

VESTRUM[™]

SERIES TRACTOR





VESTRUM SERIES TRACTOR SPECIFICATIONS

Cab only	MODEL	VESTRUM 100 ACTIVEDRIVE 8 & CVXDRIVE™	VESTRUM 130 ACTIVEDRIVE 8 & CVXDRIVE
ENGINE Tier 4 B/Final with 4 cylinder, turbocharged 4.9L FPT Oppe Tier 4 B/Final with 4 cylinder, turbocharged 4.9L FPT Engine HP* 100 273 cu. in. Engine HP* 86 12 Ministration Selective Catalytic Reduction (SCR) Number of Valvies 16 Alternator 200 amp Settery 12 votr - 17 Am 1300 FM CCA TEALYMINSION/PTO TEALYMINSION/PTO Cylind (A) 24 x 24 Active/Prive 8 dual-clutch transmission 25 MPH (40 FPH) Option (A) 24 x 24 Active/Prive 8 dual-clutch transmission 25 MPH (40 FPH) Orteger Option and environmental path environmental Private Priv	Operator Station		
Type Type Final with 4 cylinder, turbocharged 4.5L FFT Type Ty	Traction	MFD only	
Displacement P7	ENGINE		
Engine HP × 100 130 PTO IP × 86 112 Insissions Teatment 86 selective Catalytic Reduction (SCR) Number of Yalves 16 Althornator 16 18 Battery 12 year 1 76 h 31 300 EN CCA TRAWSH/SOM/PTO 24 x	Туре	Tier 4 B/Final with 4 cylinder, turbocharged 4.5L FPT	
PTO HP	Displacement	273 cu. in.	
Emissions Treatment Selective Catalytic Reduction (SCR) Number of Valves 16 Atternator 200 amp Battery 12 voit - 178 An 1300 EN CCA TRAINSISION/PTO Value of Vivorive CVT transmission 25 MPH (40 KPH) Coregor Optional on ActiveDrive 8 transmission 25 MPH (40 KPH) Creeper Optional on ActiveDrive 8 transmission 25 MPH (40 KPH) Creeper Optional on ActiveDrive 8 transmission 25 MPH (40 KPH) Creeper Optional on ActiveDrive 8 transmission 25 MPH (40 KPH) Creeper Optional on ActiveDrive 8 transmission Front Class 1.75 front axie with Electo hydraulic diff lock Rear Renotes (Standard/Optional) Class 1.75 front axie with Electo hydraulic diff lock Rear Remotes (Standard/Optional) 2 Mechanical + 1 Electronic / 2 Mechanical + 2 Electronic Hydraulic Prumpfrlow Closed center load sensing pump Rear Remotes (Standard/Optional) 2 Mechanical + 2 Electronic 2 Mechanical + 2 Electronic Hydraulic Prumpfrlow 6 (20 de la mental reare) 2 Mechanical + 2 Electronic Standard (Distronal)	Engine HP*	100	130
Number of Valves 16 Alternator 200 amp Battery 12 volt - 176 Ah 1300 EN CCA TEAMSINISTROYPO Option (A) 24 x 24 ActiveDrive 8 dual-clutch transmission 25 MPH (40 KPH) Creeper OVXDrive OVT transmission 25 MPH (40 KPH) Creeper 540v540E/1000 pm Interchangable PTO shaft AXLES Front Class 1.75 front axie with Elector phrasile diff lock Rear Flange HYDRAULICS/HITCH Type Closs 6 center load sensing pump Rear Remotes (Standard/Optional) 2 Mechanical + 1 Electronic / 2 Mechanical + 2 Electronic Hybraulic Pump/Flow 2 Response (Standard/Optional) 3-Point Hitch Category (Standard/Optional) EDC w/lover link sensing / Cat Il flex link ends Standard Lift Capacity 6,700 lb. (3 039 kg) lift capacity with dual 80 mm external rams CAPACHTEE 47 gal. (180 L) Diese Exhaust Fluid Tank 5 gal. (19 L) Diese Exhaust Fluid Tank 5 gal. (19 L) Diese Exhaust Fluid Tank 18 6 in. (4 784 mm) Overall Height			

^{*} at 2,200 ERPM rated engine speed

SAFETY NEVER HURTS![™] Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

